# ADAM-5090/5091 ADAM-5095

## 4-port RS-232 Module **2-port CAN Module with Isolation Protection**



### **Specifications**

#### General

- Certification
- Connectors
- Enclosure
- ABS+PC LED Indicators TX, RX (each port)
- Power Consumption 0.6 W (max.)

#### **Communications**

- Data Bits
- Data Signals
- Parity
- Ports
- 4
- UARTs
- Speed
- 50 ~ 115.2 kbps
- Stop Bits 1, 1.5, 2
- Support standard Com Port with Share interrupt (ADAM-5091) Note:

For ADAM-5510 Series, ADAM-5510KW Series, and ADAM-5511 only (ADAM-5090) For ADAM-5550 Series (ADAM-5091)

1 x 16C954 (128-byte FIFO)

### **Ordering Information**

- ADAM-5090
- ADAM-5091 4-port RS-232 Module with Share Interrupt
- OPT1A
- OPT1D
- 1 m RJ-48 to Male DB9 Cable

4-port RS-232 Module

30 cm RJ-48 to Male DB9 Cable

## **Specifications**

#### General

- Certification
- Connector
- Enclosure LED Indicator

#### **Communications**

- CAN Controller SJA-1000 **CAN Transceiver** 82C250 Protocol CAN2.0 A/B CAN-H, CAN-L Signal Support
- Speed
- Protection
- Isolation Protection 1,000 V<sub>DC</sub>

Note:

only for ADAM-5550 series

### **Ordering Information**

2-port CAN Module with Isolation Protection







- CE, FCC Class A
- 2 x DB9-M

1Mbps

- ABS+PC
  - TX (Yellow), RX (Green) For Each Port
- Power Consumption 1 W (max.)

CE, FCC Class A (ADAM-5091 only), FM

5, 6, 7, 8 TxD, RxD, RTS, TS, DTR, DSR, DCD, RI, GND

4 x RJ-45

none, even, old