



## Main

|   |  |
|---|--|
| Range   | TeSys  |
| Product name  | TeSys GB2  |
| Device short name                                   | GB2  |
| Product or Component Type                           | Circuit breaker  |
| Device Application                                  | Control  |
| Poles description                                   | 2P   |
| Network type  | AC/DC  |
| Utilisation category                                | Category A IEC 60947-2<br>DC-12 IEC 60947-5-1<br>DC-13 IEC 60947-5-1   |
| Network frequency                                   | 50/60 Hz IEC 60947-2   |
| Breaking capacity                                   | 2 KA Icu 110 V AC 50/60 Hz IEC 60947-2<br>1.5 KA Icu 230/240 V AC 50/60 Hz IEC 60947-2<br>1.5 KA Icu 400/415 V AC 50/60 Hz IEC 60947-2<br>1.5 kA Icu 24 V DC IEC 60947-2 |
| [Ics] rated service short-circuit breaking capacity | 75 % 110 V AC 50/60 Hz IEC 60947-2<br>75 % 230/240 V AC 50/60 Hz IEC 60947-2<br>75 % 400/415 V AC 50/60 Hz IEC 60947-2   |
| Trip unit technology                                | Thermal-magnetic   |
| Magnetic tripping current                           | 165 A  |

## Complementary

|   |  |
|---|--|
| Mounting Mode                                       | By clips   |
| Mounting Support                                    | Rail<br>Plate  |
| Mounting position                                   | Horizontal<br>Vertical   |
| Control Type  | Toggle   |
| Line Rated Current                                  | 12 A   |
| [U <sub>e</sub> ] rated operational voltage         | 415 V AC 50/60 Hz IEC 60947-2<br>48 V DC   |
| [U <sub>imp</sub> ] rated impulse withstand voltage | 4 kV IEC 60947-2   |
| Power dissipation per pole                          | 2 W  |
| Mechanical durability                               | 8000 cycles  |
| Electrical durability                               | 8000 cycles  |
| Connections - terminals                             | Connector 1 0.00...0.01 in <sup>2</sup> (0.75...6 mm <sup>2</sup> )solid without cable end<br>Connector 2 0.00...0.01 in <sup>2</sup> (0.75...4 mm <sup>2</sup> )solid without cable end<br>Connector 1 0.00...0.01 in <sup>2</sup> (0.75...4 mm <sup>2</sup> )flexible with cable end<br>Connector 2 0.00...0.00 in <sup>2</sup> (0.75...2.5 mm <sup>2</sup> )flexible with cable end |
| Tightening torque                                   | 10.62 lbf.in (1.2 N.m) connector   |
| Mechanical robustness                               | Shocks 22 Gn for 20 ms IEC 60068-2-27<br>Vibrations 5 Gn, 5...110 Hz IEC 60068-2-6   |
| Quantity per Set                                    | Set of 3   |
| 9 mm pitches  | 4  |
| Height  | 2.91 in (74 mm)  |
| Width   | 1.18 in (30 mm)  |
| Depth   | 2.76 in (70 mm)  |
| Net Weight  | 0.25 lb(US) (0.115 kg)   |

## Environment

|                                       |                                  |
|---------------------------------------|----------------------------------|
| Standards                             | EN/IEC 60947-1<br>EN/IEC 60947-2 |
| Protective treatment                  | TC                               |
| IP degree of protection               | IP20 IEC 60529                   |
| Ambient air temperature for operation | -4...140 °F (-20...60 °C)        |
| Ambient Air Temperature for Storage   | -40...176 °F (-40...80 °C)       |
| Fire resistance                       | 1760 °F (960 °C) IEC 60695-2-1   |
| Operating altitude                    | 9842.52 ft (3000 m)              |






## Ordering and shipping details

|                       |                                  |
|-----------------------|----------------------------------|
| Category              | 22631-TELE CIRCUIT BREAKER (GB2) |
| Discount Schedule     | I                                |
| GTIN                  | 3389110865523                    |
| Nbr. of units in pkg. | 1                                |
| Package weight(Lbs)   | 3.95 oz (112.0 g)                |
| Returnability         | No                               |
| Country of origin     | FR                               |

## Packing Units

|                              |                        |
|------------------------------|------------------------|
| Unit Type of Package 1       | PCE                    |
| Package 1 Height             | 3.15 in (8.0 cm)       |
| Package 1 width              | 3.35 in (8.5 cm)       |
| Package 1 Length             | 3.78 in (9.6 cm)       |
| Unit Type of Package 2       | BB1                    |
| Number of Units in Package 2 | 3                      |
| Package 2 Weight             | 11.92 oz (338.0 g)     |
| Package 2 Height             | 3.15 in (8.0 cm)       |
| Package 2 width              | 3.35 in (8.5 cm)       |
| Package 2 Length             | 3.78 in (9.6 cm)       |
| Unit Type of Package 3       | S02                    |
| Number of Units in Package 3 | 36                     |
| Package 3 Weight             | 9.69 lb(US) (4.397 kg) |
| Package 3 Height             | 5.91 in (15.0 cm)      |
| Package 3 width              | 11.81 in (30.0 cm)     |
| Package 3 Length             | 15.75 in (40.0 cm)     |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           |  <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant  <a href="#">EU RoHS Declaration</a>   |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information |  Yes   |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>  |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |

## Contractual warranty

---

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---