


**HC-D 7-TFL-57/O1M20G**

Order No.: 1604888

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1604888>

HEAVYCON sleeve housing D7, for single locking latch, height 57 mm, with support, straight conductor exit, zinc

**Commercial data**

GTIN (EAN)	 4 017918 881023
sales group	D011
Pack	10 pcs.
Customs tariff	85389099
Catalog page information	Page 508 (PC-2009)

**Product notes**WEEE/RoHS-compliant since:  
03/01/2006

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

**Technical data****General data**

Note	For contact inserts HC-D7, D8, A3, A4, B5, HS2-D7
Design	D7
Height	57 mm
Width	28 mm

Length	26.5 mm
Housing type	Sleeve housings
Locking type	for single locking latch
Cable exit	Straight
Type of the screw connection	1x M20
Degree of protection	IP54 / IP65 with sealing screw
Ambient temperature (operation)	-40 °C ... 125 °C
Housing material	Zinc die-cast
Housing surface material	Powder-coated, gray

### Certificates / Approvals



Certification GOST


### Accessories

Item	Designation	Description
<b>Assembly</b>		
1686229	HC-D 7-DS-IP65	Sealing screw, for IP65 protection
<b>General</b>		
1647967	HC-M-DE-M20	Pressure screw set, for housing with M20 thread, consisting of notched seal, 2 washers and pressure screw

**Diagrams/Drawings**

Dimensioned drawing

---



**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2010 Phoenix Contact  
Technical modifications reserved;