


EPC2010C – Enhancement Mode Power Transistor

 V_{DS} , 200 V $R_{DS(on)}$, 25 mΩ I_D , 22 A

Gallium Nitride's exceptionally high electron mobility and low temperature coefficient allows very low $R_{DS(on)}$, while its lateral device structure and majority carrier diode provide exceptionally low Q_G and zero Q_{RR} . The end result is a device that can handle tasks where very high switching frequency, and low on-time are beneficial as well as those where on-state losses dominate.

Maximum Ratings

PARAMETER		VALUE	UNIT
V_{DS}	Drain-to-Source Voltage (Continuous)	200	V
I_D	Continuous ($T_A = 25^\circ\text{C}$, $R_{\theta JA} = 5.3$)	22	A
	Pulsed (25°C , $T_{PULSE} = 300 \mu\text{s}$)	90	
V_{GS}	Gate-to-Source Voltage	6	V
	Gate-to-Source Voltage	-4	
T_J	Operating Temperature	-40 to 150	$^\circ\text{C}$
T_{STG}	Storage Temperature	-40 to 150	

Thermal Characteristics

PARAMETER		TYP	UNIT
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	1.1	$^\circ\text{C}/\text{W}$
$R_{\theta JB}$	Thermal Resistance, Junction-to-Board	2.7	
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient (Note 1)	56	

Note 1: $R_{\theta JA}$ is determined with the device mounted on one square inch of copper pad, single layer 2 oz copper on FR4 board. See https://epc-co.com/epc/documents/product-training/Appnote_Thermal_Performance_of_eGaN_FETs.pdf for details.

Static Characteristics ($T_J = 25^\circ\text{C}$ unless otherwise stated)

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
BV_{DSS}	Drain-to-Source Voltage	$V_{GS} = 0 \text{ V}$, $I_D = 200 \mu\text{A}$	200			V
I_{DSS}	Drain-Source Leakage	$V_{GS} = 0 \text{ V}$, $V_{DS} = 160 \text{ V}$		50	150	μA
I_{GSS}	Gate-to-Source Forward Leakage	$V_{GS} = 5 \text{ V}$		1	3	mA
	Gate-to-Source Reverse Leakage	$V_{GS} = -4 \text{ V}$		50	150	μA
$V_{GS(TH)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}$, $I_D = 3 \text{ mA}$	0.8	1.4	2.5	V
$R_{DS(on)}$	Drain-Source On Resistance	$V_{GS} = 5 \text{ V}$, $I_D = 12 \text{ A}$		18	25	mΩ
V_{SD}	Source-Drain Forward Voltage	$I_S = 0.5 \text{ A}$, $V_{GS} = 0 \text{ V}$		1.7		V

All measurements were done with substrate connected to source.



EPC2010C eGaN® FETs are supplied only in passivated die form with solder bars

Applications

- High Speed DC-DC conversion
- Class D Audio
- Lidar

Benefits

- Ultra High Efficiency
- Ultra Low $R_{DS(on)}$
- Ultra Low Q_G
- Ultra Small Footprint



Dynamic Characteristics (T_j = 25°C unless otherwise stated)

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
C _{ISS}	Input Capacitance	V _{DS} = 100 V, V _{GS} = 0 V		380	540	pF
C _{OSS}	Output Capacitance			240	320	
C _{RSS}	Reverse Transfer Capacitance			1.8	2.7	
R _G	Gate Resistance		0.4			Ω
Q _G	Total Gate Charge	V _{DS} = 100 V, I _D = 12 A, V _{GS} = 5 V		3.7	5.3	nC
Q _{GS}	Gate-to-Source Charge	V _{DS} = 100 V, I _D = 12 A		1.3		
Q _{GD}	Gate-to-Drain Charge			0.7	1.3	
Q _{G(TH)}	Gate Charge at Threshold			0.9		
Q _{OSS}	Output Charge	V _{DS} = 100 V, V _{GS} = 0 V		40	52	
Q _{RR}	Source-Drain Recovery Charge			0		

All measurements were done with substrate connected to source.

Note 2: C_{OSS(ER)} is a fixed capacitance that gives the same stored energy as C_{OSS} while V_{DS} is rising from 0 to 50% BV_{DSS}.

Note 3: C_{OSS(TR)} is a fixed capacitance that gives the same charging time as C_{OSS} while V_{DS} is rising from 0 to 50% BV_{DSS}.

Figure 1: Typical Output Characteristics at 25°C




Figure 2: Transfer Characteristics




Figure 3: R_{DS(on)} vs. V_{GS} for Various Drain Current




Figure 4: R_{DS(on)} vs. V_{GS} for Various Temperatures




Figure 5a: Capacitance Linear Scale




Figure 5b: Capacitance Log Scale




Figure 6: Gate Charge




Figure 7: Reverse Drain-Source Characteristics




Figure 8: Normalized On Resistance vs. Temperature




Figure 9: Normalized Threshold Voltage vs. Temperature




Figure 10: Gate Current




Figure 11: Transient Thermal Response Curves







Figure 12: Safe Operating Area



TAPE AND REEL CONFIGURATION

4 mm pitch, 12 mm wide tape on 7" reel




EPC2010 (Note 1)	Dimension (mm)		
	Target	MIN	MAX
a	12.00	11.90	12.30
b	1.75	1.65	1.85
c (Note 2)	5.50	5.45	5.55
d	4.00	3.90	4.10
e	4.00	3.90	4.10
f (Note 2)	2.00	1.95	2.05
g	1.50	1.50	1.60

Note 1: MSL 1 (moisture sensitivity level 1) classified according to IPC/ JEDEC industry standard.

Note 2: Pocket position is relative to the sprocket hole measured as true position of the pocket, not the pocket hole.


DIE MARKINGS




Part Number	Laser Markings		
	Part # Marking Line 1	Lot_Date Code Marking Line 2	Lot_Date Code Marking Line 3
EPC2010C	2010	YYYY	ZZZZ

DIE OUTLINE

Solder Bar View



Side View




DIM	MICROMETERS		
	MIN	Nominal	MAX
A	3524	3554	3584
B	1602	1632	1662
c	1379	1382	1385
d	577	580	583
e	262	277	292
f	245	250	255
g	600	600	600

Pad no. 1 is Gate;
 Pads no. 3, 5, 7 are Drain;
 Pads no. 4, 6 are Source;
 Pad no. 2 is Substrate.*

*Substrate pin should be connected to Source

RECOMMENDED LAND PATTERN

(units in μm)




The land pattern is solder mask defined.

Pad no. 1 is Gate;
 Pads no. 3, 5, 7 are Drain;
 Pads no. 4, 6 are Source;
 Pad no. 2 is Substrate.*

*Substrate pin should be connected to Source

RECOMMENDED STENCIL DRAWING

(units in μm)



Recommended stencil should be 4 mil (100 μm) thick, must be laser cut, opening per drawing. The corner has a radius of R60.

Intended for use with SAC305 Type 3 solder, reference 88.5% metals content.

Additional assembly resources available at <https://www.epc-co.com/epc/DesignSupport/AssemblyBasics.aspx>

Efficient Power Conversion Corporation (EPC) reserves the right to make changes without further notice to any products herein to improve reliability, function or design. EPC does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others. eGaN® is a registered trademark of Efficient Power Conversion Corporation. EPC Patent Listing: epc-co.com/epc/AboutEPC/Patents.aspx

Information subject to change without notice. Revised April, 2021