### **Data sheet** 2097.0 SI K 5x25 2,000A-F





Fuse, Dimensions: 5x25 mm, Trigger characteristic: Fast-acting (F); Rated voltage: 250 V, Rated current: 2 A

#### **Business data**

Article number	2097.0
Article name	SI K 5x25 2,000A-F
GTIN (EAN)	4044211049058
Indicator colour	Blue
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	1.32 g
Weight per piece (including packaging)	1.4 g
Unit of weight	G
Customs number	85361010
Country of origin	DE
Product description	fuse

### Data sheet



### 2097.0 SI K 5x25 2,000A-F

Technical data		
Dimensions		
Length	25 mm	
Diameter of contact cap	5.2 mm	
Optical defect display available	✓	
Dimensions	5x25 mm	
Ratings		
Rated voltage	250 V	
Rated current	2 A	
Materials		
Contact caps	Brass	
Surface	Nickel	
Tube	Ceramic	
Further technical data		
Trigger characteristic	Fast-acting (F)	
Rated breaking capacity	1500 A @ AC 250 V	
Voltage drop	420 mV	
Power loss (@ 1.5 ln)	1.1 W	
Melting integral I2ts	2.4 A²s	
Environmental Product Compliance		
REACH Conform	yes	
REACH Reference date	2023-01-17	
REACH Candidate Substance Note	No	
RoHS Conform	yes	

# **Data sheet** 2097.0 SI K 5x25 2,000A-F



Media

# **Data sheet** 2097.0 SI K 5x25 2,000A-F



**Accessories**