





SECTION A-A  
SCALE 2.000

DESCRIPTION	PRODUCT NO.		
KIT	72844-X01LF	72844-X02LF	72844-X03LF
COVER WITH GROUND SPRING	1	1	1
CONTACT STRIP	5	5	5
HEADER	1		
HEADER		1	
HEADER			1

Dimension with oval around are critical dimensions including any attached geometrical tolerance. Other features or stanf -alone geometrical tolerances being critical have a note "CRITICAL FEATUR" below the item  
A symbol x (x: drawing current revision) will be next to any dimension, view or note which has been molded with the current drawing revision

ROHS INFORMATION:  
-This product meets European Union Directives and other country regulations as described in GS-22-008.  
-The housing will withstand exposure to 260°C peak temperature for 5 second in a wave solder application with a 1.4 mm minimum thick circuit board. see application notes/procedures if they are available.  
-Packaging spec: see GS-14-920

www.fciconnect.com		surface 0.8 ISO 1302	tolerance std ISO 406 ISO 1101	projection mm
		TOLERANCES UNLESS OTHERWISE SPECIFIED		
Dr	B.Beirinckx	2002/06/30	ANGULAR	size A4
Eng	G.Nys	2002/06/30	LINEAR	Scale 1.000
Chr	W.Panis	2002/06/30	0° ±2°	ECN LS07-0255
Appr	W.Panis	2002/06/30	Product family	Spec ref
		title SOFIX STB SHIELDED I/O Shielded RA Hdr 4x6 Pos		dwg no 72844_C
catalog no				Rev. W
				sheet 2 of 2



Copyright FCI.