

Product data sheet

Characteristics

9080GLP3

Terminal block, Linergy, blown fuse indicator, 240 V, for 9080GF6 sectional fuse holder block



Main

Range	9080G
Product	Blown Fuse Indicator
Quantity per Set	Set of 10

Complementary

Material	Nylon
Height	1.17 in (29.72 mm)
Width	0.64 in (16.26 mm)
Depth	2.4 in (60.96 mm)

Ordering and shipping details

Category	21702-9080 G (NOT GCB)
Discount Schedule	CP5
GTIN	785901489672
Nbr. of units in pkg.	1
Package weight(Lbs)	0.02 lb(US) (0.011 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.35 in (16.129 cm)
Package 1 width	2.50 in (6.35 cm)
Package 1 Length	16.13 in (40.968 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Weight	4.80 oz (136.078 g)
Package 2 Height	2.50 in (6.35 cm)
Package 2 width	2.50 in (6.35 cm)
Package 2 Length	3.40 in (8.636 cm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------