

wire connector CU with control wire voltage tap-off 4 units accessory for:
3VA5 125



Model	
product brand name	SETRON
product designation	accessories
Product version	circular conductor terminal
Accessories	Wire connector
General technical data	
designation / of the terminal	TC1.0
Connections according IEC	
stripped length	12.2
Connections according UL	
permissible temperature / of connectable conductor / according to UL 486A-486B	90 °C
stripped length	0.48
connectable conductor cross-section	
• for copper cable / solid / minimum	14
• for copper cable / solid / maximum	10
• for copper cable / stranded / minimum	14
• for copper cable / stranded / maximum	8
• for copper cable / finely stranded / minimum	14
• for copper cable / finely stranded / maximum	8
tightening torque / when using copper cables	
• solid	14 AWG: 20 lb-in 12 AWG: 35 lb-in 10 AWG: 55 lb-in
• stranded	14 AWG: 20 lb-in 12 AWG: 35 lb-in 10 - 8 AWG: 55 lb-in
• finely stranded	14 AWG: 20 lb-in 12 AWG: 35 lb-in 10 - 8 AWG: 55 lb-in

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9134-0JK10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA9134-0JK10>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9134-0JK10

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

last modified:

7/5/2022

