



## PL03 Series 3mm (T1) LED

### Features

- \*Popular 3mm Lens Style with Flange
- \*1 GaAsP Yellow Chip used
- \*Color Diffused Lens with a Wide Viewing Angle
- \*High Intensity
- \*Low Current Requirement
- \*Reliable and Rugged
- \*RoHS Compliant

### Absolute Maximum Ratings at $T_A = 25^\circ\text{C}$

Power Dissipation.....	78mW
Reverse Voltage (<100 $\mu$ A).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	-25 $^\circ\text{C}$ to +85 $^\circ\text{C}$
Storage Temperature Range.....	-40 $^\circ\text{C}$ to +100 $^\circ\text{C}$
Soldering Temperature (1.6mm below body).....	260 $^\circ\text{C}$ for 5 seconds

### Electrical & Optical Characteristics at $T_A = 25^\circ\text{C}$

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle $2\theta_{1/2}$	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
Color Diffused Lens			nm	nm	Deg				
PL03-CDY01	Yellow	GaAsP	585	590	56 $^\circ$	2.1	2.6	10.0	27.0

All dimensions are in **Millimeters**. Tolerance is  $\pm 0.25\text{mm}$  unless otherwise specified. An epoxy meniscus may extend about 1 mm down the leads.

