

# FOC-I-D1PGY-S/MPBGC - Fiber optic coupling



1041840

<https://www.phoenixcontact.com/us/products/1041840>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Fiber optic coupling, degree of protection: IP20, number of positions: 2, material: Plastic, connection method: Coupling, cable outlet: straight, Ethernet

## Your advantages

- High reliability with comprehensive quality assurance measures
- Optimized precision (stability) with the use of ceramic sleeves
- Future-proof with RoHS 2 conformity
- Tailored for compatibility with the DIN rail adapters

## Commercial data

Item number	1041840
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB16
Product key	ABNIDA
Catalog page	Page 375 (C-2-2019)
GTIN	4055626598680
Weight per piece (including packing)	6.3 g
Weight per piece (excluding packing)	6.3 g
Customs tariff number	85367000
Country of origin	CN

## Technical data

### Notes

General	For integration into DIN rail adapter NBC-PP-G1PGY
---------	--

### Product properties

Type	FSMA
Product type	Female insert
Sensor type	Ethernet
Number of positions	2
Connection profile	MTP: type B
No. of cable outlets	2
Number of slots	1
Cable outlet	straight

### Insulation characteristics

Overvoltage category	III
Degree of pollution	2

### Electrical properties

Rated surge voltage	0.8 kV
Nominal current $I_N$	0.5 A
Transmission medium	FO

### Connection data

#### Connection technology

Connection method	Coupling
-------------------	----------

### Material specifications

Color of the housing part	beige
Flammability rating according to UL 94	V0
Contact material	Copper alloy
Housing material	Plastic

### Cable/line

Cable type	Fiberglass
External sheath, color	silver-colored
Tensile strength short-term/long-term	40 N
Resistance to oil	no

#### FO cable

Number of fibers	2
------------------	---

### Mechanical properties

# FOC-I-D1PGY-S/MPBGC - Fiber optic coupling



1041840

<https://www.phoenixcontact.com/us/products/1041840>

Tensile strength short-term/long-term	40 N
---------------------------------------	------

## Mechanical data

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
	IP20
Ambient temperature (operation)	-10 °C ... 70 °C
Resistance to UV radiation	no
Resistance to oil	no

## Standards and regulations

Resistance to UV radiation	no
Resistance to oil	no

## Mounting

Mounting type	Snap in
Connection method	Coupling

# FOC-I-D1PGY-S/MPBGC - Fiber optic coupling



1041840

<https://www.phoenixcontact.com/us/products/1041840>

## Classifications

### ECLASS

ECLASS-11.0	19170116
ECLASS-12.0	19170116
ECLASS-13.0	19170116

### ETIM

ETIM 8.0	EC000752
----------	----------

### UNSPSC

UNSPSC 21.0	26121600
-------------	----------

# FOC-I-D1PGY-S/MPBGC - Fiber optic coupling



1041840

<https://www.phoenixcontact.com/us/products/1041840>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

# FOC-I-D1PGY-S/MPBGC - Fiber optic coupling



1041840

<https://www.phoenixcontact.com/us/products/1041840>

## Mandatory accessories

### NBC-PP-G1PGY - DIN rail adapter

1041740

<https://www.phoenixcontact.com/us/products/1041740>



DIN rail adapter, design: Headers with shielding, degree of protection: IP20, material: PC-GF10, connection method: Quick connection, without assembled modules

---

## Accessories

### NBC-PP-G1PGY - DIN rail adapter

1041740

<https://www.phoenixcontact.com/us/products/1041740>



DIN rail adapter, design: Headers with shielding, degree of protection: IP20, material: PC-GF10, connection method: Quick connection, without assembled modules

# FOC-I-D1PGY-S/MPBGC - Fiber optic coupling



1041840

<https://www.phoenixcontact.com/us/products/1041840>

## CUC-PP-FR19:1U-I-EMPTY:24 - Marshalling panel

1422978

<https://www.phoenixcontact.com/us/products/1422978>

Patch bay, 19" mounting, IP20, with 24 slots selectively for RJ45 cable connection modules, RJ45 coupling modules, LC duplex, SC simplex and MPO, medium gray



---

## CUC-PP-FR19:1U-I-EMPTY:24 BK - Marshalling panel

1422979

<https://www.phoenixcontact.com/us/products/1422979>

Marshalling panel, design: RJ45, degree of protection: IP20, material: PC-GF, connection method: Quick connection, housing size: 1, color: black



---

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)