



Main

| | |
|------------------------------|----------------------|
| Range of Product | Square D Pumptrol |
| Product or Component Type | Float switch |
| Device Application | Open tank heavy duty |
| Device short name | 9036G |
| Product Specific Application | Liquid level control |
| Electrical circuit type | Power circuit |
| Quantity per Set | Set of 1 |
| Type of Packing | Individual |

Complementary

| | |
|-------------------------------|---|
| Product destination | For open tank or sump |
| Device mounting | Pedestal |
| Cable entry number | 2 conduit entries for 3/4"-14 NPT UL 508 |
| Contacts type and composition | 2 NC, snap action, DPST-DB, Form YY |
| Controlled fluid | Fresh water specific gravity of 0.85 in or higher Sea water specific gravity of 0.85 in or higher Hydraulic oil specific gravity of 0.85 in or higher Corrosive fluid specific gravity of 0.85 in or higher |
| Motor power kW | 1.5 KW 2 hp)115 V AC, 1 phase 2.2 KW 3 hp)115 V AC, 3 phase 2.2 KW 3 hp)230 V AC, 1 phase 3.7 KW 5 hp)230 V AC, 3 phase 0.75 KW 1 hp)460 V AC, 3 phase 0.75 KW 1 hp)475 V AC, 3 phase 0.18 KW 0.25 hp)32 V DC 0.37 KW 0.5 hp)115 V DC 0.37 KW 0.5 hp)230 V DC 3.7 KW 5 hp)460 V AC, 1 phase 3.7 kW 5 hp)475 V AC, 1 phase |
| Electrical connection | Screw-clamp terminals 10 AWG |
| Contact operation | Contacts close on liquid rise |
| Float movement | Variable adjustable |
| Float position | Any |
| Float rod angle | Vertical |
| Force down to trip | 27 Ozf long lever 29 Ozf medium lever 31 ozf short lever |
| Force up to trip | 20 Ozf long lever 22 Ozf medium lever 24 ozf short lever |
| Short-circuit protection | 20 A cartridge fuse gG |
| Local signalling | Without |
| Enclosure Material | Cast Aluminium |
| Operating position | Vertical position only |
| Electrical durability | 100 cycles 60 cyc/mn |
| Mechanical durability | 300 cycles |
| Terminal block type | 4 terminals |
| Maximum operating rate | 60 cyc/mn |

| | |
|-------------------------------|---|
| [Ui] rated insulation voltage | 575 V UL 508 |
| Net Weight | 8.82 lb(US) (4.00 kg) |
| Terminals description ISO n°1 | Line-load-load-line |
| Factory modification | Without |
| Kit composition | Rod and float are to be chosen in accessories Float switch |

Environment

| | |
|---------------------------------------|---|
| Standards | CE UL 508 |
| Ambient air temperature for operation | -22...220 °F (-30...104 °C) |
| Ambient Air Temperature for Storage | -22...220 °F (-30...104 °C) |
| NEMA degree of protection | NEMA 4 UL 50 |
| Product Certifications | UL listed file E12158 CSA file LR25490 |

Ordering and shipping details

| | |
|-----------------------|--|
| Category | 21591 - 9036 COMMERCIAL FLOAT SWITCHES |
| Discount Schedule | CP7G |
| GTIN | 785901489580 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 8.73 lb(US) (3.96 kg) |
| Returnability | No |
| Country of origin | MX |

Packing Units

| | |
|------------------------------|----------------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 26.67 in (67.742 cm) |
| Package 1 width | 10.50 in (26.67 cm) |
| Package 1 Length | 67.74 in (172.064 cm) |
| Unit Type of Package 2 | PAL |
| Number of Units in Package 2 | 80 |
| Package 2 Weight | 699.03 lb(US) (317.074 kg) |
| Package 2 Height | 40.00 in (101.6 cm) |
| Package 2 width | 36.00 in (91.44 cm) |
| Package 2 Length | 48.00 in (121.92 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|