

FFKDSA1/V2-7,62

Order No.: 1790487

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1790487>

PC terminal block, Nominal current: 15 A, Nom. voltage: 320 V,
Pitch: 7.62 mm, Number of positions: 1, Type of connection: Spring-
cage connection, Assembly: Soldering, Conductor/PCB connection
direction: 90 °, Color: green, The article can be aligned to create
different nos. of positions!

Commercial data	
EAN	4017918044350
Pack	50 pcs.
Customs tariff	85369010
Weight/Piece	0.001403 KG
Catalog page information	Page 117 (CC-2009)

Product notes

WEEE/RoHS-compliant since:
01/01/2003



[http://
www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)
Please note that the data given
here has been taken from the
online catalog. For comprehensive
information and data, please refer
to the user documentation. The
General Terms and Conditions of
Use apply to Internet downloads.

Certificates / Approvals



Certification

CCA, CUL, GOST, KEMA, UL

CUL

Nominal voltage U_N	300 V
Nominal current I_N	10 A
AWG/kcmil	22-16

UL

Nominal voltage U_N	300 V
Nominal current I_N	10 A
AWG/kcmil	22-16

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;