



注記;

- 1 適用規格 : 108-5315
- 製品規格 : 114-5147
- 取付適用規格 : 15-507J
- 2 取扱い説明書 : 66710V, 94V-0, グレー
- △ 材料及び色

NOTES;

- 1 APPLICABLE SPECIFICATIONS
- PRODUCT SPEC. : 108-5315
- APPLICATION SPEC. : 114-5147
- 2 INSTRUCTION SHEET : 15-507J
- △ MATERIAL&COLOR : 66NYLON, 94V-0, GRAY

凡 -1 AS SHOWN
本

LTR		REVISION RECORD	DR	CHK	DATE	Copyright © 1980 AMP (Japan) LTD. ALL RIGHTS RESERVED.		AMP AMP (JAPAN), LTD. Tokyo, Japan	
0	RELEASED	FOR No 3-2163	T.F.	S.M.	8-10-78	DR.	T. FUTATSUGI	DE.	I. ENOMOTO
						CHK.	S. ANNO	APP.	S. ANNO
WIRE RANGE		INSULATION DIA		FINISH		NAME		GENERAL TOLERANCE	
mm ² (AWG)		mmφ		mmφ		AMP ラテックス コネクタ - AMP LATTICE CONN. PLUG HOUSING 28POS		0-0.1 : ±0.2 10-0.1 : ±0.25 30-0.1 : ±0.3 ANGLES : ±0.5	
MATERIAL		MATERIAL		MATERIAL		SCALE		REV.	
△		△		△		A3 J		0	
NO. 8		NO. 8		NO. 8		2-1		1 OF 1	
SECT.		SECT.		SECT.		C-176763		SHEET	
A-A		A-A		A-A		1		1	

CUSTOMER DRAWING