



Product: <u>5541PT</u> ☑

Thermostat & Control, #22-2pr, TC, Indiv. Foil, CMR

Product Description

Thermostat & Control Cable, Riser-CMR, 2-22 AWG stranded tinned copper pairs with foam polyolefin insulation, Individually Beldfoil® shielded and PVC jacket

Technical Specifications

Product Overview

| Suitable Applications: | Thermostat, Control, Noisy Environment |
|------------------------|--|
| | |

Construction Details

Conductor

| Element | No. of Elements | Size | Stranding | Material |
|---------|-----------------|------|-----------|--------------------|
| Pair(s) | 2 | 22 | 7x30 | TC - Tinned Copper |

Insulation

| Material | Nom. Thickness | Nom. Insulation Diameter | Color Code | Notes |
|-----------------------------|----------------------|--------------------------|--------------------------------|-------|
| PE - Polyethylene (Foam) | 0.0175 in (0.445 mm) | 0.064 in (1.6 mm) | Black and White, Green and Red | HDPE |

Outer Shield

| Shield Type | Shield Type Material | | Drainwire Type |
|-------------|-------------------------|------|------------------|
| Tape | Bi-Laminate (Alum+Poly) | 100% | 18 AWG (7x26) TC |

Outer Jacket

| Material | Nom. Thickness | Nom. Diameter |
|--------------------------|--------------------|---------------|
| PVC - Polyvinyl Chloride | 0.020 in (0.51 mm) | 0.202 in |

Electrical Characteristics

Electricals

| Nom. Conductor DCR | Nom. Capacitance Cond-to-Cond | Nom. Velocity of Prop. | Max. Current |
|--------------------|-------------------------------|------------------------|--------------------------------|
| 17.9 Ohm/1000ft | 16.9 pF/ft (55.4 pF/m) | 78% | 2.1 Amps per Conductor at 25°C |

Voltage



Mechanical Characteristics

Temperature

| UL Temperature | Operating |
|----------------|----------------|
| 75°C | -20°C To +75°C |

Bend Radius

| Stationary Min. | Installation Min. |
|-------------------|-------------------|
| 2.02 in (51.3 mm) | 2.02 in |

| Max. Pull Tension: | 58.8 lbs (26.7 kg) |
|--------------------|--------------------|
| Bulk Cable Weight: | 23.3 lbs/1000ft |

Standards and Compliance

| Environmental Suitability: | Indoor |
|----------------------------------|--|
| Flammability / Reaction to Fire: | UL 1666 riser, FT4 |
| CPR Compliance: | CPR Euroclass: Eca |
| NEC / UL Compliance: | Article 800, CMR |
| CEC / C(UL) Compliance: | CMG |
| European Directive Compliance: | EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| UK Regulation Compliance: | UKCA Mark |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |
| Plenum Number: | 6541PT |

History

| Update and Revision: | Revision Number: 0.332 Revision Date: 05-05-2023 |
|----------------------|--|
| | |

Part Numbers

Variants

| | Item # | Color | UPC | Footnote |
|---|----------------|-------|--------------|----------|
| Ę | 5541PT 0011000 | Brown | 612825164265 | С |

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.